



Product Features

- for hydraulic balancing of hot water return systems (PWH-C), supports thermal disinfection
- wetted metal parts made from dezincification-free, corrosion-resistant and lead-free gunmetal, resistant against aggressive water
- isolating unit with temperature sensor pocket
- PTFE seat gasket
- thermostatic balancing unit
- female pipe thread
- with plugged drain port
- free from dead spots

Standards and Approvals

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

Technical data

- control range 111 °F - 129 °F
- pressure rating PN 16
- max. operating temperature 194 °F

Part no.	DN	A1	A2	H1 (mm)	H1 (in.)	H2 (mm)	H2 (in.)	L1 (mm)	L1 (in.)	T1 (mm)	T1 (in.)	cv (m³/h)	cv (GPM)	Weight (kg)	Weight (lbs)
1540401500	15	FPT 1/2	G 1/4	85	3.3	29	1.1	110	4.3	15	0.6	1.3	1.5	0.69	0.31
1540402000	20	FPT 3/4	G 1/4	85	3.3	34	1.3	123	4.8	16.3	0.6	1.6	1.9	0.90	0.41
1540402500	25	FPT 1	G 1/4	96.5	3.8	35	1.4	133	5.2	19.1	0.8	3.2	3.7	1.16	0.53

© Copyright by Kemper Water Control Systems, Inc., 2378 Linwood Ave. Naples, FL 34112, USA