

Product Features

- low pressure loss
- wetted metal parts made from dezincification-free, corrosion-resistant and lead-free gunmetal, resistant against aggressive water
- full bore
- female pipe thread
- removable inner top part TOP-ENTRY, with EPDM gasket body and gunmetal ball
- operating handle 90° rotatable
- free from dead spots

Standards and Approvals

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

Technical data

- pressure rating PN 16
- max. operating temperature 194 °F

Part no.	DN	A1	D1 (mm)	D1 (in.)	H1 (mm)	H1 (in.)	H2 (mm)	H2 (in.)	L1 (mm)	L1 (in.)	T1 (mm)	T1 (in.)	Weight (kg)	Weight (lbs)
3890001500	15	FPT 1/2	90	3.5	55.5	2.2	25	1.0	84	3.3	14.5	0.6	0.50	0.23
3890002000	20	FPT 3/4	90	3.5	55.5	2.2	25	1.0	90	3.5	16.5	0.6	0.58	0.27
3890002500	25	FPT 1	90	3.5	58.5	2.3	28	1.1	99	3.9	18	0.7	0.84	0.38

© Copyright by Kemper Water Control Systems, Inc., 2378 Linwood Ave. Naples, FL 34112, USA