



Product Features

- prevents stagnation in ring pipe installations through forced flow during downstream withdrawals, can be used in cold drinking water (PWC) and hot drinking water (PWH)
- KHS Flow-Splitter - dynamic, according to the Venturi principle, including dynamic cartridge, flow and return branch for connection of outlets / plumbing units
- wetted metal parts made from dezincification-free, corrosion-resistant and lead-free gunmetal, resistant against aggressive water
- KHS Flow-Splitter pass with female thread
- plumbing unit feed pipe with female thread
- plumbing unit return pipe with female thread
- maintenance free
- free from dead spots
- including KHS stop valve, female threaded, figure 389 00
- maintenance-free EPDM spindle seal
- removable inner top part TOP-ENTRY, with EPDM gasket body and gunmetal ball
- incl. insulation shell made of closed-cell foamed polyethylene

Standards and Approvals

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

Technical data

- pressure rating PN 16
- max. operating temperature 194 °F

Part no.	passage DN	Outlets DN	VAV DN	A1	A2	A3	H1 (mm)	H1 (in.)	L1 (mm)	L1 (in.)	L2 (mm)	L2 (in.)	L3 (mm)	L3 (in.)	Weight (kg)	Weight (lbs)
6510601500	15	15	15	FPT 1/2	FPT 1/2	FPT 1/2	48,5	1,9	185	7,3	100	3,9	84	3,3	1,72	0,78
6510602000	20	20	20	FPT 3/4	FPT 3/4	FPT 3/4	58,5	2,3	185	7,3	100	3,9	90	3,5	2,07	0,97
6510602500	25	20	20	FPT 1	FPT 3/4	FPT 3/4	68,5	2,7	185	7,3	100	3,9	90	3,5	2,37	1,08
6510603200	32	20	20	FPT 1 1/4	FPT 3/4	FPT 3/4	73,5	2,9	195	7,7	100	3,9	90	3,5	2,50	1,14
6510604000	40	25	25	FPT 1 1/2	FPT 1	FPT 1	78,5	3,1	206	8,1	100	3,9	99	3,9	3,63	1,6
6510605000	50	25	25	FPT 2	FPT 1	FPT 1	88,5	3,5	219	8,6	100	3,9	99	3,9	4,30	1,96