



**Product Features**

- prevents stagnation in ring pipe installations through forced flow during downstream withdrawals, can be used in cold drinking water (PWC) and hot drinking water (PWH)
- KHS Flow-Splitter - dynamic, according to the Venturi principle, including dynamic cartridge, flow and return branch for connection of outlets / plumbing units
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- KHS Flow-Splitter pass with female thread
- plumbing unit feed pipe with female thread
- plumbing unit return pipe with female thread
- maintenance free
- free from dead spots
- incl. insulation shells
- use only KHS isolating valves in the loop to maintain proper function of the KHS Flow-Splitter

**Standards and Approvals**

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

**Technical data**

- pressure rating PN 16
- max. operating temperature 194 °F

Part no.	passage DN	Outlets DN	A1	A2	H1 (mm)	H1 (in.)	L1 (mm)	L1 (in.)	L2 (mm)	L2 (in.)	Weight (kg)	Weight (lbs)
6512001500	15	15	FPT 1/2	FPT 1/2	48,5	1,9	185	7,3	100	3,9	0,59	0,27
6512002000	20	20	FPT 3/4	FPT 3/4	58,5	2,3	185	7,3	100	3,9	0,81	0,37
6512002500	25	25	FPT 1	FPT 3/4	68,5	2,7	185	7,3	100	3,9	1,03	0,47
6512003200	32	32	FPT 1 1/4	FPT 3/4	73,5	2,9	195	7,7	100	3,9	1,22	0,55
6512004000	40	40	FPT 1 1/2	FPT 1	78,5	3,1	206	8,1	100	3,9	1,76	0,8
6512005000	50	50	FPT 2	FPT 1	88,5	3,5	219	8,6	100	3,9	2,42	1,1